



**Autex  
Acoustics®**

ASL

## Manufacturer's Guarantee

ASL is manufactured by Autex Australia Pty Ltd under an ISO 9001 and ISO 14001 certified Environmental and Quality Management System. The product is guaranteed to be free from manufacturing defects.

<b>Suitable applications</b>	ASL applications include exposed and semi-exposed acoustic and thermal linings within the building envelope.	
<b>Durability</b>	When installed in accordance with the manufacturer's instructions, either exposed or semi-exposed, the product carries a manufacturer's guarantee for a period of no less than ten years.	Where installed within an enclosed cavity, in accordance with the manufacturer's instructions, it will satisfy the 50-year durability criteria for minimum design life as set out in the ABCB guidance document durability in buildings 2015 (section 3.4).
<b>Performance and supply format</b>	Refer to the individual product information sheets for specific information.	
<b>Composition</b>	100% polyester fibre from polyethylene terephthalate (PET). ASL contains a minimum of 50% recycled polyester fibre.	
<b>Finish</b>	ASL is made from thermally bonded non-woven material, so colour blending variations in finish are typical with in the same batch. This is an inherent feature of the product and is not considered a manufacturing fault. Contact your specification manager for additional information.	
<b>Fire ratings</b>	<b>AS ISO 9705: 2003</b> Australian Group Number: Group 1 SMOGRARC: less than 100m <sup>2</sup> /s <sup>2</sup> Assessed using methodology AS ISO 9705:2003 in accordance with AS5637.1:2015, as required by NCC specification C1.10-4.	Refer to individual product Information sheet additional information.
<b>VOC emissions</b>	Autex Acoustics polyester has been tested by Cetec Pty Ltd (Report: RCV080408) for chemical emission as follows:	VOC concentration: 0.01 mg/m <sup>3</sup> (7 days) GREENGUARD VOC Limit: 0.25 mg/m <sup>3</sup> (7 days)



## Physical description/ properties

Boiling point	N/A
Melting point:	250°C / 482°F
Vapour pressure:	N/A
Specific gravity:	Polyester 1.38
Flash point:	N/A
Explosive limits:	N/A
Solubility in water	Not soluble
Alkalinity:	pH 7.8
Relative vapour density:	N/A

## Care and maintenance

Maintain in accordance with the Care and Maintenance Guide available for this product.

This warranty excludes prolonged exposure to direct sunlight, continuous exposure to environments that contain chemicals that adversely react, break down or rot polyester fibre.

Extended exposure to temperatures above 100°C including damage caused by abrasion. Project specific warranties can be produced where these conditions or applications are present or expected.

### ● Autex Industries Ltd

702-718 Rosebank Rd  
Private Bag 19988  
Avondale 1746, Auckland  
New Zealand  
Freephone 0800 428 839  
Phone +64 9 828 9179  
Fax +64 9 828 5810

### ● Autex Australia Pty Ltd

285 Swan St  
Richmond, Melbourne VIC  
3081, Australia  
Freephone 1800 678 160  
Phone +61 3 9457 6700  
Fax +61 3 9457 1020

### ● Autex Acoustics Ltd

Unit J4, Lowfields Way,  
Lowfields Business Park,  
Elland, West Yorkshire  
Hx5 9Da  
United Kingdom  
Phone +44 0 1422418899

### ● Autex Acoustics LLC

19350 Van Ness Avenue  
Torrance, CA 90501  
United States of America  
Phone +1 424 203 1813