



Lanes™ is manufactured by Autex Industries Ltd and Autex Australia Pty Ltd under an ISO 9001 and ISO 14001 certified Quality and Environmental Management Systems. The product is guaranteed to be free from manufacturing defects and carries a Manufacturer's Guarantee for a period of no less than ten years to meet all of the performance properties stated within this guarantee.

**Specification**

<b>Product name</b>	Lanes
<b>Description</b>	100% polyester lightweight semi-rigid panel
	<b>Metric</b>
Lanes dimensions	Lanes are 300 mm wide sections x 2400 mm and 2700 mm lengths. Custom lengths available
Thickness	12 mm thick Cube, depth varies by design

**Physical description/  
properties**

Boiling point:	N/A
Melting point:	250°C
Vapour pressure:	N/A
Specific gravity:	Polyester 1.38
Flash point:	N/A
Explosive limits:	N/A
Solubility in water:	Not soluble
Alkalinity:	pH 7.8
Relative vapour density:	N/A

**Acoustic performance**

Lanes is specifically designed to reduce and control reverberated noise and echo in building interiors.

Minimum Noise Reduction Coefficient 0.80

Frequency (Hz)	125	250	500	1000	2000	4000	NRC
● Lanes Plane	0.10	0.40	0.85	1.00	0.95	0.95	0.80
● Lanes Peak	0.15	0.45	0.85	0.95	0.90	0.95	0.80
● Lanes Sawtooth	0.15	0.45	0.90	1.00	0.95	0.95	0.85



## Service

For further information about Lanes or any other Autex Acoustics® product, please contact your specification manager or visit our website.

## Care and maintenance

Maintain in accordance with the Care and Maintenance Guide available for this product.

## Product specifications

### Composition

100% polyester fibre from polyethylene terephthalate (PET). Lanes contains a minimum of 60% previously recycled polyester fibre.

### Suitable applications

Feature acoustic wall, not recommended for high impact areas.

### Fire ratings

Cube has been evaluated using the following test methods.

### ISO 9705: 1993

Classification: Group 1-S

Smoke production rate:

<5.0m<sup>2</sup>/s

As required by NZBC C/VM2

### AS ISO 9705 - 2003

Classification: Group 1

(SMOGR<sub>arc</sub>): <100m<sup>2</sup>/s<sup>2</sup>

as required by BCA Specification NCC 2019 1.10-4 NCC2022 S7C4

### ASTM E-84-15a

Class A, FS:0 - SD:45

(Cube 1/2")

RJ4479-2

### BS EN 13501-1:2018

Tested using BS EN ISO 11925-2:2020 and BS EN 13823:2020 and classified in accordance with BS EN 13501-1:2018, as required by BS EN 15102:2007 + A1:2011.

Fire compliance information is available on request. Please contact your Autex Acoustics specification manager.

### Thermal performance

Cube 12 mm R0.3 (@23°C)

### VOC emissions

Autex Acoustics polyester has been tested for chemical emissions in accordance with ASTM D5116 and is considered a low VOC product.

VOC concentration: 0.009 mg/m<sup>3</sup> (7 days)

### Water vapour sorption

ASTM C1104 / C1104M-13a

Test conditions: 49°C, 95%RH

Water vapour absorbed and adsorped after 4 days:

0.4% by weight

### Microbial resistance

ASTM G21-15

Growth rating: 0 (No growth)

Lanes does not promote the growth of moulds and mildew.

### Colour fastness to light

Lanes is suitable for indoor use only. Light fastness is dependent on use and exposure. Lanes has been evaluated to the following standard: ISO 105-B02:2014  
Rating: 6 (Highest = 7)

### Colour fastness to rubbing

ISO 105-X12:2016

Dry rating: 4-5 (Highest = 5)

Wet rating: 4-5 (Highest = 5)

### Pattern repeat

Non-woven. No pattern repeat but product has directional grain. Product may vary from samples and batch to batch due to fibre blending and lay-up, which is an inherent feature of this product.

### Fabric care

Blot spills from fabric quickly. Wipe with a damp cloth. Avoid rubbing and excessive amounts of water as this will affect the finish. Use carpet or upholstery shampoo as directed. Blot with a clean dry cloth after each application of solution.

Custom printed Lanes requires the services of a specialist cleaning company. Refer to the Autex Acoustics Care and Maintenance Guide for more information.



### Australia

VIC, TAS, SA  
285 Swan St  
Richmond  
VIC 3121  
Phone 03 9450 6700  
Freephone 1800 678 160

NSW, ACT  
Suite 8.03,  
89 York Street,  
Sydney 2000  
Phone 02 9729 6100

QLD, NT  
68 Business St  
Yatala  
QLD 4207  
Phone 07 3001 3000

WA  
Unit 1, 398C Victoria Rd  
Malaga  
WA 6090  
Phone 08 9355 1911

Customer Service 1800 678 160 [www.autexacoustics.com.au](http://www.autexacoustics.com.au)



### New Zealand

Autex Industries Ltd  
702-718 Rosebank Rd  
Private Bag 19988  
Avondale 1746, Auckland  
Phone +64 800 428 839  
Freephone +64 9 828 5810



### United Kingdom

Autex Acoustics Ltd  
Unit J4, Lowfields Way  
Lowfields Business Park  
Elland, West Yorkshire  
HX5 9DA  
Phone +44 142 241 8899



### United States

Autex Acoustics LLC  
1630 Dan Kipper Dr  
Riverside CA 92507  
Phone +1 424 203 1813

Autex Acoustics® products are carbon neutral and contribute to WELL, LEED, Green Star & BREEAM certification. Contact your Autex Acoustics® specification manager to hear how we can support your low carbon goals.

Autex is an ISO certified organisation encompassing Quality (ISO 9001), Environmental (ISO 14001), & Health and Safety (ISO 45001). Brand names and logos are registered or unregistered trademarks owned or used under license by Autex Industries Limited. Swatches featured are representative of the final product colours as close as the printing process allows. Please refer to actual samples prior to ordering. This brochure uses low environmental impact FSC certified pulps, manufactured in a facility that is chlorine free and ISO 14001 Environmental Management System accredited. Emissions have been offset and this brochure is fully recyclable and carbon neutral.  
© Copyright 2023 Autex Industries Ltd. All Rights Reserved.